



The Refrigeration Experts

Product specification



BCT15/7: 15kg/ 7kg Blast Chiller and Freezer

17-273

15kg Blast chiller/freezer cabinet

Features and benefits

- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- Freezing capacity from +70°C to -18°C in less than 240 minutes within specifications
- Dedicated 15Kg blast chiller with occasional 7Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior and interior the 'gold standard' in performance finishes
- Intuitive touch control panel – just press and go!
- 5 Shelf Positions for GN 1/1 Pans

We use cookies to ensure you get the best experience on our website.
[More information.](#)

Accept all

Decline all

Refrigerant	R290
Electrical supply	230/50/1
Fuse rating (A)	13
Current (A)	1.7
Power (W)	400
Refrigerant mass (g)	110
Thermal heat rejection (W)	400

Finish ext/int	304 S/S & 304 S/S
Number of sections	1
Section configuration	Right hinge
System	Integral

Dimensions

Height (mm)	875
Width (mm)	805
Depth (mm)	755
Gross volume (ltr)	106
Net volume (ltr)	105
Chilling capacity (kg)	15
Freezing capacity (kg)	7
Leg type	Braked castors
GN size	1/1
Gross weight (kg)	95
Net weight (kg)	65

Energy

Climate Class	5
Freezing capacity (kg)	7
GWP	3

We use cookies to ensure you get the best experience on our website.
[More information.](#)

RS485 connection for HACCP data logging	Yes
System	Remote
Electrical supply	220/60/1

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com |
www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.
[More information.](#)