



The Refrigeration Experts

Product specification



EP700HL: 600 Ltr Cabinet Dual Temperature

41-697

Dual temperature cabinet

Features and benefits

- This model offers refrigerator and freezer temperatures in the same cabinet - perfect for when space is at a premium
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready

We use cookies to ensure you get the best experience on our website.
[More information.](#)

Accept all

Decline all

- This is a dual refrigeration system and requires two power supplies.
Data about each system can be found in the spec table “Temperature” and “Temperature 2”

Technical

Refrigerant	R290
Temperature	Refrigerator +1/+4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.6
Power (W)	240
Refrigerant mass (g)	65
Temperature 2	Freezer -18/-21°C
Fuse rating (A) 2	10
Current (A) 2	2.80
Power (w) 2	475
Refrigerant mass (g) 2	65

Build

Cabinet type	Dual temperature
Door material	304 Stainless steel
Finish ext/int	304 S/S & 304 S/S
Section configuration	Right hinge
System	Integral

Dimensions

Height (mm)	2080
Width (mm)	700

Energy

Climate Class	5
Energy grade	C

We use cookies to ensure you get the best experience on our website.
[More information.](#)

GN size	2/1
Gross weight (kg)	133
Net weight (kg)	133
Gross volume (ltr) 2	270

EI 2	53.73
AEC (kWh) 2	1261
Energy consumption (kWh/24hr)	1.0479
Energy consumption (kWh/24hr) 2	3.45

Options

Electrical supply 220/60/1

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com |
www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for nor to form part of any contract unless specifically

We use cookies to ensure you get the best experience on our website.
[More information.](#)