

Product specification



EP700L: 600 Ltr Cabinet Freezer

41-723

Single door freezer marine cabinet

Features and benefits

- Suitable for marine and offshore applications, this model incorporates marine legs, bulkhead brackets, positive latch handle and marine shelves
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Accept all Decline all

• Operates efficiently in ambient temperatures of up to 43°C

Technical

Refrigerant R290 **Temperature** Freezer -18/-21°C **Electrical** 220-240/60/1 supply Fuse rating (A) 10 Current (A) 1.2 Power (W) 270 Refrigerant 80 mass (g) Thermal heat 280 rejection (W)

Build

Cabinet type Marine
Finish ext/int 304 S/S & 304 S/S

Number of 1 sections
Section Right hinge configuration
System Integral

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Dimensions

Height (mm) 2080 Width (mm) 700 Depth (mm) 855 **Gross volume** 600 (ltr) Net volume 479.9 (ltr) Marine legs Leg type **GN** size 2/1 **Gross weight** 130.5 (kg) Net weight 121.5 (kg)

Energy

Climate Class	5
Energy grade	В
EEI	30.25
AEC (kWh)	1161
GWP	3
Energy	3.18
consumption	
(kWh/24hr)	

Options

Hinge Right

System Remote

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet:
 100mm
- Denth with door open is 1500mm

We use cookies to ensure you get the best experience on our website. More information.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website. <u>More information.</u>