

Product specification



EP700L: 600 Ltr Cabinet Freezer

41-106

Single door freezer cabinet

Features and benefits

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel –

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Accept all Decline all

• Operates efficiently in ambient temperatures of up to 43°C

Technical

Refrigerant R290 **Temperature** Freezer -18/-21°C **Electrical** 230/50/1 supply Fuse rating (A) 10 Current (A) 1.2 Power (W) 270 Refrigerant 80 mass (g) Thermal heat 280 rejection (W)

Build

Cabinet type	Standard
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Dimensions

Height (mm) 2080 Width (mm) 700 Depth (mm) 855 **Gross volume** 600 (ltr) **Net volume** 479.9 (ltr) Leg type Braked castors **GN** size 2/1 **Gross weight** 130.5 (kg) **Net weight** 121.5 (kg)

Energy

Climate Class	5
Energy grade	В
EEI	30.25
AEC (kWh)	1161
GWP	3
Energy	3.18
consumption	
(kWh/24hr)	

Options

Hinge Left

Electrical supply 220/60/1

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet:

We use cookies to ensure you get the best experience on our website. More information.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website. <u>More information.</u>