



The Refrigeration Experts

Product specification



EP700G: 600 Ltr Cabinet Refrigerator

41-153

Single glass door refrigerator cabinet

Features and benefits

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel –

We use cookies to ensure you get the best experience on our website.

[More information.](#)

Accept all

Decline all

- Operates efficiently in ambient temperatures of up to 32°C (ISO Climate class 4)

Technical

Refrigerant	R290
Temperature	Refrigerator +1/+4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	0.59
Power (W)	135
Refrigerant mass (g)	80
Thermal heat rejection (W)	150

Build

Cabinet type	Glass
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Dimensions

Energy

Climate Class	3
Energy grade	B
EEL	11.3
AEC (kWh)	675
GWP	3
Min - max temperature (°C)	-1/5

We use cookies to ensure you get the best experience on our website.
[More information.](#)

Height (mm)	2080
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	600
Net volume (ltr)	482.3
Castors	Braked Left castors
GN size	2/1
Gross weight (kg)	104
Net weight (kg)	97.5

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com |
www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.
[More information.](#)