



The Refrigeration Experts

## Product specification



### FFC6/2: 152 Ltr Counter Vari Temp Drawer

35-101

Variable temperature two drawer  
counter

## Features and benefits

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 3 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works efficiently in hot kitchens, operating in ambient temperatures exceeding ISO Climate Class 5 (43°C ambient)

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Accept all

Decline all

## Technical

<b>Refrigerant</b>	R290
<b>Temperature</b>	Freezer -18/-21°C
<b>Electrical supply</b>	230/50/1
<b>Fuse rating (A)</b>	10
<b>Current (A)</b>	1.5
<b>Power (W)</b>	250
<b>Refrigerant mass (g)</b>	65
<b>Temperature 2</b>	Refrigerator +1/+4°C
<b>Fuse rating (A) 2</b>	10
<b>Current (A) 2</b>	1.5
<b>Power (w) 2</b>	250
<b>Refrigerant mass (g) 2</b>	65
<b>Thermal heat rejection (W)</b>	400

## Build

<b>Finish ext/int</b>	304 S/S & 304 S/S
<b>Section configuration</b>	1/2
<b>System</b>	Integral

## Dimensions

<b>Height (mm)</b>	900
<b>Width (mm)</b>	1100
<b>Depth (mm)</b>	700
<b>Gross volume (litre)</b>	76

## Energy

<b>Climate Class</b>	5
<b>Energy grade</b>	C
<b>EEI</b>	38.5
<b>AEC (kWh)</b>	1087

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

<b>Gross weight (kg)</b>	169.5
<b>Net weight (kg)</b>	159.5
<b>Gross volume (ltr) 2</b>	76

<b>Energy consumption (kWh/24hr)</b>	2.978
<b>Energy consumption (kWh/24hr) 2</b>	2.98

## Options

**Worktop**

Biscuit lid

## Footnotes

- FFC6-2 requires two mains leads
- Ecodesign data relevant per compartment
- Adequate airflow must be kept around the counter: 150mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) |  
[www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications

We use cookies to ensure you get the best experience on our website.  
[More information.](#)