



The Refrigeration Experts

Product specification



LR200: 200 Ltr Undercounter Cabinet Freezer

13-207

Undercounter freezer cabinet

Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Integrated door lock for added security
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 40°C (ISO Climate Class 5)

We use cookies to ensure you get the best experience on our website.
[More information.](#)

Accept all

Decline all

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.5
Power (W)	235
Refrigerant mass (g)	83
Thermal heat rejection (W)	220

Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Dimensions

Height (mm)	824
Width (mm)	684
Depth (mm)	755
Gross volume (ltr)	200
Net volume (ltr)	95.9
Leg type	Roller castors rear, levelling bolts front
Gross weight (kg)	69
Net weight (kg)	62

Energy

Climate Class	5
Energy grade	D
EEl	54.6
AEC (kWh)	1605.32
GWP	3
Energy consumption (kWh/24hr)	4.4

We use cookies to ensure you get the best experience on our website.
[More information.](#)

Options

Hinge

Left

Footnotes

- For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com |
www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.
[More information.](#)