

## Product specification



LR360: 360 Ltr Undercounter Cabinet Freezer

13-187

Undercounter freezer cabinet

## Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 40°C (ISO Climate Class 5)

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Accept all Decline all

Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.7
Power (W)	320
Refrigerant mass (g)	135
Thermal heat rejection (W)	320

Number of sections	2
Section configuration	Left hinge,Right hinge
System	Integral

_	_								
	ĭ	m	$\overline{}$		$\circ$	ï			$\circ$
IJ	ı	III	$\leftarrow$	П	5	I (	. )	ΙI	5

Height (mm)	824
Width (mm)	1217
Depth (mm)	755
Gross volume (ltr)	360
Net volume (ltr)	188.9
Leg type	Roller castors rear, levelling bolts front
Gross weight (kg)	105.5
Net weight (kg)	90.5

## Energy

Climate Class	5
Energy grade	D
EEI	69.51
AEC (kWh)	2413
GWP	3
Energy consumption (kWh/24hr)	6.611

We use cookies to ensure you get the best experience on our website. More information.

## Footnotes

• For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website. <u>More information.</u>