



DOUBLE DOOR REFRIGERATOR BAKER M 140 CCG C1 50B

Product series: Baker

Item number: 961401018



The GRAM BAKER M 140 CCG C1 50B is a DOUBLE DOOR REFRIGERATOR with a net internal volume of 697.0000 Ltr.

Generations of bakeries, confectioners, and patisseries are trusting GRAM BAKER storage and process cabinets to accommodate their bakery products. The GRAM air circulation system is key to maintain correct and uniform temperature and humidity levels inside the cabinet. The air is exhausted and refrigerated before being directed back into the cabinet, circulating around all food items. Thus, unwanted dehydration and skin forming of doughs can be avoided almost entirely.

Preserving Quality

Both storage and process cabinets come with built-in functionalities that preserve the quality of your bakery products at all times.

Low Running Costs

The energy-efficient refrigeration technology implemented in this wide line-up of storage cabinets can help saving running costs on a day-to-day basis.

Built-in Safety

All BAKER Cabinets come with a controller equipped with safety functions: Door alarm, alarms for high-temperature levels, or when the cleaning of the condenser filter is required to avoid overheating. A top panel perfectly protects the controller from water splashes.

Multi-Functional

The SF can be used as a quick chiller/freezer, storage freezer, storage refrigerator, or thawing cabinet. If required, the GA can be also used continuously as a freezer, as a refrigerator, or as a prover.

Designed for Bakers

The GRAM BAKER series strikes with features, specifically designed for the requirements of bakery businesses. The cabinet meets standard bakery tray sizes and the support rails can be individually positioned.

The BAKER M 140 CCG C1 50B comes with the following extras:

- Right-hand hinged door with lock
- Air circulation system
- Dry cooling and controlled thawing (M versions)
- Automatic defrost and reevaporation of water

SPECIFICATIONS

| | |
|--|--------------------------|
| Product title | DOUBLE DOOR REFRIGERATOR |
| Temperature range | -5/+12°C |
| Volume, gross (l) | 1359 |
| Net usable volume (l) | 697 |
| Interior | Stainless |
| Dimensions W x D x H (mm) | 1400 x 905 x 2100 |
| Weight, packed (kg) | 220 |
| Refrigerant | R290 |
| GWP | 3 |
| Connection | 230V, 50 Hz |
| Connection load (Watt) | 248 |
| Energy consumption Ecodesign AEC (kWh) | 562 |

| | |
|--|---|
| Energy Efficiency Class | B |
| Energy Efficiency Index EEI | 32.1 |
| Sound level – dB(A) | 42.8 |
| Insulation (mm) | 70 mm (cyclopentane) |
| Refrigeration capacity at -10°C (Watt) | 560 |
| Climate class | 5 |
| Door Type | Double Door |
| Legs / Castors | H = 110 mm (C1) |
| Exterior | Stainless |
| Refrigerant (kg) | 0.149 |
| CO2 equivalent (kg) | 0.45 |
| Equipped with | One right and one left hand hinged door with lock, self closing doors and pedal door openers, LED light, drycooling and controlled rapid thaw, 50 pairs of adjustable trayslides, C1 castors. |