



BAKER STANDARD K 69 LFG L2 15B

Product series: Baker

Item number: 960690096

The GRAM BAKER STANDARD K 69 LFG L2 15B is a with a net internal volume of 342 Ltr.

Generations of bakeries, confectioners, and patisseries are trusting GRAM BAKER storage and process cabinets to accommodate their bakery products. The GRAM air circulation system is key to maintain correct and uniform temperature and humidity levels inside the cabinet. The air is exhausted and refrigerated before being directed back into the cabinet, circulating around all food items. Thus, unwanted dehydration and skin forming of doughs can be avoided almost entirely.

Preserving Quality

Both storage and process cabinets come with built-in functionalities that preserve the quality of your bakery products at all times.

Low Running Costs

The energy-efficient refrigeration technology implemented in this wide line-up of storage cabinets can help saving running costs on a day-to-day basis.

Built-in Safety

All BAKER Cabinets come with a controller equipped with safety functions: Door alarm, alarms for high-temperature levels, or when the cleaning of the condenser filter is required to avoid overheating. A top panel perfectly protects the controller from water splashes.

Multi-Functional

The SF can be used as a quick chiller/freezer, storage freezer, storage refrigerator, or thawing cabinet. If required, the GA can be also used continuously as a freezer, as a refrigerator, or as a prover.

Designed for Bakers

The GRAM BAKER series strikes with features, specifically designed for the requirements of bakery businesses. The cabinet meets standard bakery tray sizes and the support rails can be individually positioned.

The BAKER STANDARD K 69 LFG L2 15B comes with the following extras:

- Right-hand hinged door with lock
- Air circulation system
- Dry cooling and controlled thawing (M versions)
- Automatic defrost and reevaporation of water

SPECIFICATIONS

Temperature range	+2/+12°C	Sound level – dB(A)	44.4
Volume, gross (l)	610	Insulation (mm)	70 mm (cyclopentane)
Net usable volume (l)	342	Refrigeration capacity at -10°C (Watt)	336
Interior	Stainless	Climate class	5
Dimensions W x D x H (mm)	700 x 895 x 2125	GN – Shelf size	Trayslides 40 x 60 cm
Weight, packed (kg)	136	Door Type	Solid Door
Refrigerant	R290	Legs / Castors	H = 135/200 mm (L2)
GWP	3	Exterior	White Finish
Connection	230V, 50 Hz	Refrigerant (kg)	0.08
Connection load (Watt)	300	CO2 equivalent (kg)	0.225
Energy consumption Ecodesign AEC (kWh)	672	Equipped with	Right hand hinged door with lock, automatic door closing, LED light, 15 pairs of adjustable trayslides, legs L2 height 135-200 mm.
Energy Efficiency Class	D		