



## KPS 21 CH

Product series: KP - KPS

Item number: 865780550

Easy to read LCD control panel. The encoder wheel makes navigation intuitively easy to learn.

- Choose either the IFR operation, time or temperature controlled chill/freeze cycle.
- Prevent surface freezing damage with the IFR blast chilling function.
- HACCP alarms. If a power failure occurs or when a temperature limit is exceeded this will activate an audio-visual alarm.
- Up to 20 customised cycles can be stored.
- Operates as a storage cabinet after the chilling/freezing process has finished.



### SPECIFICATIONS

|                           |                      |
|---------------------------|----------------------|
| Connection                | 230V, 50/60Hz        |
| Insulation                | 55 mm (cyclopentane) |
| Temperature range         | 0/+10°C              |
| Exterior                  | Stainless            |
| Interior                  | Stainless            |
| Dimensions W x D x H (mm) | 745 x 720 x 900      |
| Weight, packed (kg)       | 120                  |
| Refrigerant               | R452A                |
| GWP                       | 2141                 |

|  |                                    |
|--|------------------------------------|
| Connection load (Watt)                               | 900                                |
| Sound level – dB(A)                                  | 65                                 |
| Refrigeration capacity at -10°C (Watt)               | 711                                |
| Climate class  | e                                  |
| Refrigerant (kg)                                     | 1.4                                |
| CO2 equivalent (kg)                                  | 2997.4                             |
| Energy consumption - Chilling (kWh/kg)               | 0.09                               |
| Chilling capacity (from +70°C to +3°C in 90 minutes) | 18 kg from +70°C to 3°C in 90 min. |