UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com







Model:

GDM-49F-HC~TSL01

Glass Door Merchandiser:

Swing Door Freezer with Hydrocarbon Refrigerant & LED Lighting




GDM-49F-HC~TSL01

- Designed using the highest quality materials and components to provide the user with an attractive, point of purchase merchandiser that brilliantly displays frozen food, resulting in high impulse sales.
- Factory engineered system using environmentally friendly R290 hydro carbon refrigerant.
- Oversized, factory balanced, refrigeration system holds -23.3°C. Ideal for frozen food products.
- Exterior non-peel or chip clear coated cold rolled steel; durable and permanent.
- Interior NSF approved, white aluminum interior liner with stainless steel floor.
- Self closing door. Positive seal, torsion type closure system.
- Triple pane thermal glass door assembly with extruded aluminum frame.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.
- Entire cabinet structure is foamed-inplace using a high density, environmentally friendly, polyurethane insulation.

Bottom mounted units feature:

- "No stoop" lower shelf
- Easily accessible condenser coil for cleaning

PLAN VIEW



ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").

Voltage: 220-240V/		Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").									
			Cabinet Dimensions (mm)			Total Dis-			Tempera-	Annual Energy Consumption	Crated Weight
Model	Doors	Shelves	W	D†	Н	(m²)	EEC	EEI	ture Class	(kWh)	(kg)
GDM-49F-HC~TSL01	2	8	1375	759	1998	1,41	С	32.9	L1	4579	211

[†] Depth does not include 42 mm for door handle(s).