UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com







Model:

TSSU-27-12M-C-HC

Food Prep Table:

Mega-Top Solid Door Sandwich/Salad Unit with Hydrocarbon Refrigerant


5/21




TSSU-27-12M-C-HC

- True's salad/sandwich units are designed with enduring quality that protects your long term investment.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), and three (3) global warming potential (GWP).
- Patented forced-air design holds 33°F to 41°F (.5°C to 5°C) product temperature in food pans and cabinet interior.
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel back.
- Stainless steel, patented, foam insulated lid and hood keep pan temperatures colder, lock in freshness and minimize condensation. Removable for easy cleaning.
- Interior attractive, NSF approved, clear coated aluminum liner. Stainless steel floor with coved corners.
- ightharpoonup 8 7/8 " (226 mm) deep, 1/2 " (13 mm) thick, full length removable cutting board included. Sanitary, high density, NSF approved white polyethylene provides tough preparation surface.
- Heavy duty PVC coated wire shelves.
- Foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

PLAN VIEW







PAN LAYOUT

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").

Voltage: 220-240\	łz	Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").										
			Pans	Cabinet Dimensions (mm)						Capacity		Crated Weight
Model	Doors	Shelves	(top)	W**	D†	Н	HP	Voltage	Amps	(litres)	Refrigerant	(kg)
TSSU-27-12M-C-HC	1	2	12	702	867	1185	1/4	220-240V/50-60Hz	1.6	215	R290	104

^{**} Width does not include 4 mm each side for lid pins.

[†] Depth does not include 26 mm for rear bumpers.