TRUE REFRIGERATION INTERNATIONAL

UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com



5/21





Model:

TUC-27F-HC

Undercounter:


Solid Door Freezer with Hydrocarbon Refrigerant




TUC-27F-HC

- True's undercounter units are designed with enduring quality that protects your long term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- ▶ Energy Efficient, environmentally friendly forced-air refrigeration system holds -23.3°C, ideally suited for frozen foods...
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel
- Interior attractive, NSF approved, clear coated aluminum liner. Stainless steel floor with coved corners.
- Front breathing.
- Heavy duty PVC coated wire shelves.
- Automatic defrost system time-initiated, time-terminated.
- Foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

PLAN VIEW





ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").

Voltage: 220-240V/50-60Hz			Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next $\frac{1}{2}$ ").										
	Model				Cabinet Dimensions (mm)					24 hr/ Energy Consumption	Annual Energy Consumption	Crated Weight	
Model	Type	Doors	Shelves	W	D	H	(litres)	EEC	EEI	(kWh)	(kWh)	(kg)	
TUC-27F-HC	Counter Frozen	1	2	702	766	839	143	С	45.8	4.034	1472	87	

[†] Depth does not include 26 mm for rear bumpers.

Test Standard: EN16825 - Climate Class 5 (40°C, 40% relative humidity).