UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com





Model:

TUC-27G-HC~FGD01

Undercounter:


Glass Door Refrigerator with Hydrocarbon Refrigerant




TUC-27G-HC~FGD01

- True's undercounter units are designed with enduring quality that protects your long term investment.
- Factory engineered system using environmentally friendly R290 hydro carbon refrigerant maintains temperature of 0.5°C to 3.3°C for the best in food preservation.
- Exterior stainless steel front, top and ends. GalFan coated steel back.
- Interior NSF approved, clear coated aluminum liner. Stainless steel floor with coved corners.
- Front breathing.
- Adjustable, heavy duty PVC coated shelves.
- Energy efficient, "Low-E", double pane thermal insulated glass doors.
- Foamed-in-place using a high density, environmentally friendly polyurethane insulation.

PLAN VIEW





ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next $\mathcal{V}^{"}$).

Voltage: 220-24	Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").											
		Doors/		Cabine	et Dime (mm)	nsions	Total Dis- play Area			Tempera-	Annual Energy Con- sumption	Crated Weight
Model	Model Type	Drawers	Shelves	W	D†	Н	(m²)	EEC	EEI	ture Class	(kWh)	(kg)
TUC-27G-HC~FGD01	Counter Chilled	1/0	2	702	766	839	0,32	Α	8,3	M1	458	93